

# ALU-RIBS SPECIFICATIONS



	S-Line	Silverline	Comfortline TLRA
Aluminium hull thickness (mm)	3	2,5	2,5
PVC thickness (mm)	0,9	0,9	0,9
PVC brand (Valmex® Mehler provides greater mechanical and UV protection)	Valmex® Mehler	Standard	Standard
PVC adhesion (thermically welded provides a longer lifetime)	Thermically welded	Glue	Glue
Bowlocker (space for 24l fuel tank)	✓	✓	✗
Seatbench material (aluminium requires less maintenance)	-	aluminium	aluminium
Adjustable seatbench	✗	✓	✓
Hull shape	double-deck- flat floor	double-deck- flat floor	single-deck - V-floor
Floor finishing	Teak-look EVA foam	Foam pads	Foam pads
Transom height	long	short	short
Console	3-person standard	optionally*	-
Bow-step	✓	✗	✗

## PARTS

Oar / paddle system	luxury, Bravo**	luxury, Bravo	luxury
Telescopic oars / paddles	✓	✓	✗
Bravo one-touch airvalves	✓	✗	✗
Inflation sequence on airvalves	✓	✓	✗
Overpressure relief valve	✓ ***	✓ ***	✓
Anti sprayflaps transom	✗	✗	✓
Anti spray rubbing strake	✓	✓	✗
SS lifting and towing eyes	✓	✓	✓
Hard handles	✓	✓	✓
Soft handles	✓	✓	✓
Lifeline	✗	✗	✓

## ACCESSOIRES

Double-action hand pump	✓	✓	✓
Fuel tank strap	✓	✓	✗
Repair kit	✓	✓	✓
Pressure gauge	✓	✗	✗
Seat cushion	✓ ****	✓	✗

## SERVICE

Warranty period (years)	3	2	2
-------------------------	---	---	---

\* recommended from SLR310 on

\*\* S-Line has paddles

\*\*\* high-end Bravo overpressure relief valve

\*\*\*\* standard on console and bow